

(19) World Intellectual Property
Organization
International Bureau



556606

(43) International Publication Date
25 November 2004 (25.11.2004)

PCT

(10) International Publication Number
WO 2004/102716 A2

(51) International Patent Classification⁷: **H01M 8/04**,
8/06, B60L 11/18

Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi,
4718571 (JP).

(21) International Application Number:
PCT/JP2004/002016

(74) Agent: **ITEC INTERNATIONAL PATENT FIRM**;
Pola-nagoya Bldg., 9-26, Sakae 2-chome, Naka-ku,
Nagoya-shi, Aichi, 4600008 (JP).

(22) International Filing Date: 20 February 2004 (20.02.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-140987 19 May 2003 (19.05.2003) JP

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (for all designated States except US): **TOY-
OTA JIDOSHA KABUSHIKI KAISHA** [JP/JP]; 1, Toy-
ota-cho, Toyota-shi, Aichi, 4718571 (JP).


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **NAKANISHI,
Haruyuki** [JP/JP]; C/o Toyota Jidosha Kabushiki
Kaisha, 1, Toyota-cho, Toyota-shi, Aichi, 4718571 (JP).
NAKATA, Kelichi [JP/JP]; C/o Toyota Jidosha Kabushiki
Kaisha, 1, Toyota-cho, Toyota-shi, Aichi, 4718571 (JP).
KOBAYASHI, Masafumi [JP/JP]; C/o Toyota Jidosha

[Continued on next page]

(54) Title: FUEL CELL SYSTEM AND VEHICLE WITH FUEL CELL SYSTEM MOUNTED THEREON



(57) Abstract: The voltage application unit first applies voltages (+,+,0,-,-,0) respectively to the electrostatic delivery electrodes 37 belonging to the phase 'a', the phase 'b', the phase 'c', the phase 'd', the phase 'e', and the phase 'f', and then successively applies voltages(0,+,+,0,-,-), voltages (-,0,+,+,0,-), voltages(-,-,0,+,+,0), voltages (0,-,-,0,+,+), and voltages(+,0,-,-,0,+). The voltage application unit repeats this cycle multiple times to apply the voltages to the phase 'a' through the phase 'f'. The water droplets flocculated in the oxidizing gas conduits 36 are charged by electrostatic induction and travel in the direction from the inlet to the outlet of the oxidizing gas conduits 36 while being repelled or attracted by the electrostatic delivery electrodes 37 in the vicinity of the water droplets in the course of the positive-negative variation of the voltage in the cycle.



Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.